

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number
WO 2005/023404 A3

(51) International Patent Classification⁷: **B01D 71/02**, 69/00, 67/00

(74) Agent: **WINCKELS, J., H., F.**; Vereenigde, Johan de Witlaan 7, NL-2517 JR Den Haag (NL).

(21) International Application Number:
PCT/NL2004/000623

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SB, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:
9 September 2004 (09.09.2004)

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CR, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: **Dutch**

Published:

(26) Publication Language: **English**



- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(30) Priority Data:
1024250 9 September 2003 (09.09.2003) NL

(88) Date of publication of the international search report:
19 May 2005

[Continued on next page]

(54) Title: MANUFACTURE OF A MICROSIEVE AND APPARATUS COMPRISING A MICROSIEVE



(57) Abstract: A filtering apparatus includes a microsieve with a membrane. The microsieve is coupled between a supply and drain channel. The membrane contains pores between the upstream surface and the downstream surface, as well as a spatial pattern of height variations in the upstream surface of the membrane, so that in a vicinity of a majority of the pores, within a distance of less than ten pore sizes from each of the pores in the majority, at least one of the height variations is provided. The height variations impede proper adhesion of larger particles from the liquid to the upstream surface and thereby reduce clogging problems.

WO 2005/023404 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.